

# Westford Antenna

*Mike Poirier*

## Abstract

Technical information is provided about the antenna and VLBI equipment at the Westford site of the Haystack Observatory and about changes to the systems since the IVS 2009 Annual Report.

## 1. Westford Antenna at Haystack Observatory

Since 1981 the Westford antenna has been one of the primary geodetic VLBI sites in the world. Located  $\sim 70$  km northwest of Boston, Massachusetts, the antenna is part of the MIT Haystack Observatory complex.



Figure 1. The radome of the Westford antenna.

Table 1. Location and addresses of the Westford antenna.

Longitude	71.49° W
Latitude	42.61° N
Height above m.s.l.	116 m
MIT Haystack Observatory Off Route 40 Westford, MA 01886-1299 U.S.A. <a href="http://www.haystack.mit.edu">http://www.haystack.mit.edu</a>	

The Westford antenna was constructed in 1961 as part of the Lincoln Laboratory Project West Ford that demonstrated the feasibility of long-distance communication by bouncing radio signals off a spacecraft-deployed belt of copper dipoles at an altitude of 3600 km. In 1981 the antenna was converted to geodetic use as one of the first two VLBI stations in the National Geodetic Survey Project POLARIS. Westford has continued to perform geodetic VLBI observations on a regular

basis since 1981. Westford has also served as a test bed in the development of new equipment and techniques now employed in geodetic VLBI worldwide. Funding for geodetic VLBI at Westford is provided by the NASA Space Geodesy Program.

## 2. Technical Parameters of the Westford Antenna and Equipment

The technical parameters of the Westford antenna, which is shown in Figure 2, are summarized in Table 2.



Figure 2. Wide-angle view of the Westford antenna inside the radome. The VLBI S/X receiver is located at the prime focus. The subreflector in front of the receiver is installed when observing with the TAL receiver (see Section 4), which is located at the Cassegrain focus.

The antenna is enclosed in a 28-meter diameter air-inflated radome made of 1.2-mm thick, Teflon-coated fiberglass—see Figure 1. When the radome is wet, system temperatures increase by 10–20 K at X-band and by a smaller amount at S-band. The major components of the VLBI data acquisition system are a Mark IV electronics rack, a Mark 5B recording system, and a Pentium-class PC running PC Field System version 9.10.2. The primary frequency and time standard is the NR-4 hydrogen maser. A CNS Clock GPS receiver system provides independent timing information and comparisons between GPS and the maser. Westford also hosts the WES2 GPS site of the IGS network. A Dorne-Margolin choking antenna is located on top of a tower ~60 meters from the VLBI antenna, and a LEICA GRX1200 Reference Station receiver acquires the GPS data.

Table 2. Technical parameters of the Westford antenna for geodetic VLBI.

<i>Parameter</i>	<i>Westford</i>	
primary reflector shape	symmetric paraboloid	
primary reflector diameter	18.3 meters	
primary reflector material	aluminum honeycomb	
S/X feed location	primary focus	
focal length	5.5 meters	
antenna mount	elevation over azimuth	
antenna drives	electric (DC) motors	
azimuth range	90° – 470°	
elevation range	4° – 87°	
azimuth slew speed	3° s <sup>-1</sup>	
elevation slew speed	2° s <sup>-1</sup>	
	<i>X-band system</i>	<i>S-band system</i>
frequency range	8180-8980 MHz	2210-2450 MHz
$T_{sys}$ at zenith	50–55 K	70–75 K
aperture efficiency	0.40	0.55
SEFD at zenith	1400 Jy	1400 Jy

### 3. Westford Staff

The personnel associated with the VLBI program at Westford and their primary responsibilities are:

Chris Beaudoin	broadband development
Joe Carter	antenna controls
Brian Corey	VLBI technical support
Kevin Dudevoir	pointing system software
Dave Fields	technician, observer
Glenn Millson	observer
Arthur Niell	principal investigator
Michael Poirier	site manager
Alan Whitney	site director

### 4. Status of the Westford Antenna

From January 1, 2010 through December 31, 2010, Westford participated in 61 standard 24-hour and 31 Intensive geodetic sessions. Westford regularly participated in the IVS-R1, IVS-R4, IVS-R&D, RD-VLBA, TQAK, and Intensive sessions along with fringe tests, e-VLBI sessions, and VLBI2010 broadband development testing.

Use of the Westford antenna is shared with the Terrestrial Air Link (TAL) Program operated by the MIT Lincoln Laboratory. In this project Westford serves as the receiving end on a 42-km long terrestrial air link designed to study atmospheric effects on the propagation of wideband communications signals at 20 GHz.

## 5. e-VLBI

Westford did not participate in any e-VLBI sessions during 2010 due to network limitations to the outside world from Haystack. 2011 expects to see this role change with network upgrades already scheduled and in progress. e-VLBI participation was replaced by the evaluation of the new Roach Digital Backend (RDBE) and Mark 5C units, a joint program with NRAO. Successful geodetic trials of the systems between Westford and the 5 meter at GGAO were achieved.

## 6. VLBI2010

In April 2010, Westford participated in a broadband VLBI experiment with MV3 at GGAO in which the source 4C39.25 was observed through transit. This experiment provided data to aid in the development of polarimetric analysis of the geodetic observables.

## 7. Outlook

Westford is expected to participate in 80 24-hour sessions in 2011. We also plan to have the flexibility to support occasional fringe tests, e-VLBI experiments, and the continuing VLBI2010 broadband development testing.