




AuScope

AN ORGANISATION FOR A NATIONAL
EARTH SCIENCE INFRASTRUCTURE PROGRAM

The AuScope Project and Trans-Tasman VLBI



Jim Lovell
John Dickey
Sergei Gulyaev
Tim Natusch
Oleg Titov
Steven Tingay


University of Tasmania
University of Tasmania
Auckland University of Technology
Auckland University of Technology
Geoscience Australia
Curtin University of Technology

www-ra.phys.utas.edu.au/auscope

Outline


- Why?
- AuScope VLBI
- New Zealand

Why we need more geodetic VLBI observatories in the southern hemisphere



AuScope: Structure and Evolution of the Australian Continent

- AuScope is funded through the Federal Government's National Collaborative Research Infrastructure Strategy (NCRIS). *Infrastructure to provide an integrated spatial positioning system spanning the whole continent.* Divided into 5 components, including Geospatial
- The Geospatial component received \$15.8M in NCRIS funding plus funds from Universities and State/Territory government. Infrastructure includes
 - 3 x 12m radio telescopes and a correlator
 - ~100 GNSS receivers
 - SLR upgrades
 - An absolute gravimeter and 3 tidal gravimeters
 - Improved computing facilities
- UTAS is constructing and will operate the VLBI array. New correlation facility at Curtin University of Technology.
- Main partners are UTAS, Curtin University of Technology and Geoscience Australia.





AuScope VLBI project: Antenna infrastructure & hardware

- Aim to meet VLBI2010 requirements if possible, or ensure an upgrade path
- 12m Antennas from COBHAM Satcom, Patriot Products division
 - Surface RMS 0.3 mm
 - Slew rates 5 deg/s Az, 1.25 deg/s El (accel: 1.3 deg/s/s)
 - Coaxial S/X feed
- Room temperature, dual polarisation receiver (UTAS)
- DBBC (HAT Lab, INAF/IRA)
- Mark5B+ (Conduant)
- A Vremya H maser (VCH 1005A) at each site

- Strategy is to build and debug at Hobart before deploying to Katherine and Yarragadee

AuScope VLBI correlation facility

- VLBI software correlator (DiFX: Deller et al. 2007, PASP, 119, 318);
- DiFX is an ongoing development for astronomical and geodetic VLBI, supported by a global development team;
- DiFX has provided the upgrade path for the Australian LBA (six antennas), the NRAO VLBA (10+ antennas) and the Bonn correlator. Also installed at Bologna, USNO, UTAS etc.
- At Curtin University of Technology, DiFX runs on:
 - 20 node Beowulf cluster;
 - 2 x quad-core processors per node;
 - 8 GB RAM per node;
 - 1 TB or greater disk per node;
 - 1 Gbps ethernet, with 10 Gbps to outside world;
 - 4 x Mark5B+ playback units;
 - 4 x Apple Xraid playback units;
 - Realtime e-VLBI capability.




AuScope VLBI project: Operations model



- 180 days per year observing
- ~100 of these will be participation in existing IVS programs
- Remainder will be aimed at measuring the strain-field of the Australian continent and trans-tasman plate motions, strengthening the southern reference frame

AuScope VLBI project: Operations model

- Overlap period between Hobart 12m and 26m before the 26m ceases IVS observations at the end of May
- Ramp-up of Hobart 12m observations through 2010
- Yarragadee and Katherine start around mid-year and ramp up.
- All three 12m antennas to a rate of 100 obs/year by end of year
- We will also schedule AuScope-only geodetic observations with correlation at Curtin for end-to-end testing of AuScope facilities.



AuScope VLBI project: Current status




this week



AuScope VLBI project: Status

- All three masers in Hobart
- One receiver installed and under testing on 12m. Traditional phase-cal (for now).
- One DBBC, two due soon
- 3 x Mark5B+ in Hobart
- Ordered 40 x 6 TB disk packs with 50 to come
- 12m now under PCFS control
- e-control (Neidhardt et al : S05-T04)



AuScope VLBI project: 12m antenna performance

- Meeting or exceeding all specifications except...
 - SEFD:
 - X-band: 4500 Jy
 - S-band: 5000 Jy
 - Tsys ~95 K in both bands.
 - S-band squint w.r.t. X-band of up to 0.1 deg
- Problem is with the feed. Patriot are working on changes to feed that will provide SEFD of 3800 Jy

AUT Project: Introduction and aims

- Develop VLBI capability in NZ
- Contribute to both IVS and Astrophysical VLBI communities



AUT Project: Infrastructure

- Cobham/Patriot antenna
- 12m Cassegrain
- Maximum Slew rates:
 - Azimuth = 5 deg s^{-1}
 - Elevation = 1 deg s^{-1}
- Currently equipped with dual polarisation dual frequency S/X feed for Geodesy



AUT VLBI project: Operations model + project status

- IVS observations planned to begin May/June 2010
- 20 days observing scheduled for 2010
- Receivers+ Maser + Recorder in place
- Waiting on delivery of DBBC (expected March)



Conclusions

- **We're nearly there!**
- **Four new geodetic antennas in southern hemisphere**
- **Identical antennas, equipment**
- **Future work**
 - 12m antenna deformation studies
 - Source structure & reference sources
 - Broad-band upgrade?
 - VLBI of GPS